

C A R B O N D I O X I D E S P E C I F I C A T I O N S



PART	WATER CAPACITY			DIAMETER		LENGTH		CYL WEIGHT		CO2		NITROGEN
	cu in	lbs	liters	in	mm	in	mm	lbs	kg	lbs	kg	cu ft
B50	2035	73.5	33.3	8.6	218.4	46.3	1175	48.3	21.9	50	22.7	144
B35	1426	51.5	23.4	8	203.2	37.8	960	35.2	16	35	15.9	100.9
B22	901	32.5	14.7	8	203.2	25.1	638	25.3	11.5	22	10	63.5
B20	814	29.4	13.3	8	203.2	23.2	589	23.7	10.8	20	9.1	57.6
B15	612	22.1	10	6.89	175	23.1	587	16.8	7.6	15	6.8	43.3
B10	407	14.7	6.7	6.89	175	16.5	419	12.6	5.7	10	4.5	29
B5	203	7.4	3.4	5.25	133.4	14.2	361	6.3	2.9	5	2.3	14.5
B2.5	102	3.7	1.7	4.38	111.3	10.3	262	3.3	1.5	2.5	1.1	7.2
B2	83	3	1.4	4.38	111.3	8.5	213	2.9	1.3	2	.9	5.9
B1.75	71.4	2.6	1.17	3.21	81.4	12.5	317	1.9	.9	1.75	.8	5.1
B1.5	61.2	2.2	1	3.21	81.4	11.1	281	1.7	.8	1.5	.7	4.3
B1	40.7	1.5	.66	3.21	81.5	7.8	197	1.4	.6	1	.5	2.9



Service Pressure: 1800 psi / 124 bar.

Specification: DOT-3AL & TC-3ALM; ISO design cylinders available.

Alloy: High strength aluminum alloy 6061-T6.

Threads: B5 & larger supplied with 1.125-12 UNF thread, all others with .750-16 UNF thread. More available.

Markings: As required by specification, inclusive of tare weight. Additional available.

Finish: Standard is brushed body with unpainted crown.

Graphics: Logos/labels in silkscreen or Duragrafix available.

Common Configuration: B10 & larger with valve + carrying handle, B5 & smaller with valve only. Caps, collars, diptubes available.