



# Thread Sealants & Teflon Tapes

**CYL-SEAL®** - Compressed gas pipe thread sealant is the leak proof sealant for high pressure threaded pipe joints. CYL-SEAL® is a thick white liquid that seals compressed gas pipe or fittings threads to prevent leaks.

**TEFLON TAPE**—PTFE tape self lubricates joints, making them easy to assemble and disassemble for a leak proof seal. Used on a wide variety of maintenance applications. Test method: ASTM D-1000, MIL-T-27330A. Use for Cylinder Threads, Cryogenic Applications, Filling Operations, etc.

Product	Application Description
<p>Cyl-SEAL®</p> 	<p>Compressed gas leaks result directly from vibration, chemical activity, corrosion, and mechanical flaws. Cyl-SEAL® seals the smallest pressurized gas leaks in pipe threads.</p> <p><b>Applications:</b></p> <ul style="list-style-type: none"> <li>• Vacuum systems</li> <li>• Valve threads</li> <li>• Natural gas</li> <li>• Compressed air lines</li> <li>• Refrigeration systems</li> <li>• Bottled welding gases</li> <li>• CO<sub>2</sub>, methyl chloride, propane, air, SO<sub>2</sub>, CL<sub>2</sub>, H<sub>2</sub>S, ammonia, and butane</li> </ul> <p><b>Composition:</b> Thick Liquid</p> <p><b>Features:</b> Effective on Flawed Pipe Thread Up To 5,000 PSI</p>
<p>TEFLON TAPE</p> 	<p>PTFE thread seal tapes for industrial applications. Made from 100% virgin PTFE. No pigments, no additives. May be used on all applications including water, oil, chemical, medical, and food processing where non-contamination standards are high. Exceeds MIL Spec T-27730A. Temperature range of -450°F to +550°F. Available in a variety of sizes and densities.</p> <p>TT-6 = 1/4" x 520            TT-12 = 1/2" x 520            TT-34 = 3/4" x 520.</p>

VALVES

CYLINDERS

CRYOGENIC

HOSES & PAINTS

ACCESSORIES

EVERGREEN Midwest Co.

Evergreen Midwest Co  
 8976 Osborne Drive  
 Mentor, OH 44060  
 Toll: 800.659.3358  
 Phone: 440.255.5540  
 Fax: 440.255.6434

[www.EvergreenMidwest.com](http://www.EvergreenMidwest.com)