

"THE TAPRITE ADVANTAGE"

- **Taprite regulators are built & tested in accordance w/ UL Standard 252 and UL 252A**
- **All regulator components & accessories are inspected upon receipt in accordance w/requirements of MIL-STD-105E**
- **High CO, volumetric flow provides continuity in product dispensing**
- **Polycarbonate bonnet will not chip, break, or fade**
- **10 Micron Filter built in to keep contaminants out of regulator**
- **One repair kit for primary and secondary regulators**



- T741*** 0-50 PSI working pressure, 60lb. gauge, 5/16" barb shutoff with check valve, silver cap
- T741HP-G** 0-50 PSI, 60lb. gauge, tank fitting, high performance, no outlet, red cap
- T742** 0-50 PSI, 60lb. & 2000lb. gauges, tank fitting, 5/16" barb shutoff with check valve, silver cap
- T742EN** 0-50 PSI, 60lb. & 2000lb. gauges, Euro tank fitting, 1/4" barb outlet, silver cap
- T742H** 0-50 PSI, 60lb. & 2000lb. gauges, tank fitting, 5/16" barb outlet, silver cap
- T742HP** 0-50 PSI, 60lb. & 2000lb. gauges, tank fitting, high performance, 5/16" barb w/ duck-bill check valve shutoff, red cap
- T742HP-01** 0-50 PSI working pressure, 60lb. & 2000lb. gauges, tank fitting, high performance, 1/4" flare w/ check valve, red cap
- T742HP-100** 0-50 PSI, 100lb. & 2000lb. gauges, tank fitting, high performance, 1/4" barb shutoff w/ check valve, red cap
- 3741-BR** 0-50 PSI, 60lb. & 2000lb. gauges, tank fitting 5/16" barb shutoff with check valve, economy
- T742-2** 1 P (Pressures) X 2P (Products), 60lb. & 2000lb. gauges 5/16" barb shutoff with check valve, silver cap
- T752HP** 2P (Pressures) X 2P (Products), 5 60lb. & 2000lb. gauges, tank fitting, high performance, /16" barb shutoff with duck-bill check valve shutoff, red cap
- T752HP-01** 2P (Pressures) X 2P (Products), 1 60lb. & 2000lb. gauges, tank fitting, high performance, /4" flare with check valve, red cap
- T5741PMHPT** 0-120 PSI working pressure, 160lb. & 2000lb. gauges, tank fitting, 5/16" barb with check valve shutoff, red cap
- FC741** Primary Low Pressure Range for under bar dispensing
Flow Rite Monitor Adjustment Range: 12-18 PSIG
- FC741H** Primary Medium Pressure Range for cold plate box dispensers
Flow Rite Monitor Adjustment Range: 30-45 PSIG