



TANK GAUGE  
(0-2000 PSI)

LOW PRESSURE GAUGE  
(0-60 PSI)

SAFETY

INLET:  
CGA 320  
CO2 TANK FITTING

CGA 320 NUT (1-1/8 HEX)

OUTLET:  
5/16 BARB SHUTOFF  
WITH CHECK VALVE

(7")

(7")

#### NOTES:

1. SAFETY BLOW-OFF: 60 5 PSI+
2. WORKING PRESSURE: 0-50 PSI
3. SMALL BLACK ZINC BONNET

DIMENSIONS ARE IN INCHES

TOLERANCES:  
FRACTIONAL  $\pm 1/64$   
ANGULAR: MACH  $\pm 1/2^\circ$   
BEND  $\pm$   
TWO PLACE DECIMAL  $\pm 0.015$   
THREE PLACE DECIMAL  $\pm 0.005$

NAME DATE  
DRAWN JPK 07/12/11  
ENG APPR.

PROPRIETARY  
AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN  
THIS DRAWING IS THE SOLE  
PROPERTY OF TAPRITE-FASSCO  
MFG., INC. ANY REPRODUCTION IN  
PART OR AS A WHOLE WITHOUT  
THE WRITTEN PERMISSION OF  
TAPRITE-FASSCO MFG., INC.  
IS PROHIBITED.

TITLE:  
REG, PRI, BEER, 60#, TANK  
FTG, 5/16B-CV SHUTOFF,  
2000#, SM BLACK, UL GAUGES  
SIZE DWG. NO. REV  
**A** 3741-BR\_SALES **C**  
SCALE: 1:2 DO NOT SCALE  
DRAWING